

W.

x

//////

TILLAMOOK COUNTY

39+73.8 Set a 3/4"X 30" iron pin for the ~~North~~ West 1/16 corner on the ~~East~~ E.& W. centerline of section 2, with a 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

52+92.0 The quarter corner between sections 3 and 2, previously described.

Returning to the West 1/16 corner on the E.& W. centerline of section 2, we ran

N. 0° 30' W. toward the center of the N.W. 1/4 of the section.

13+16.8 Set 3/4"X 30" iron pin for the center of the N.W. quarter of section 2, with a 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

Thence we ran S. 89° 44' W. toward the West boundary of the section.

13+12.2 The North 1/16 corner on the line between sections 3 and 2, previously described.

Returning to the South 1/16 corner on the line between sections 3 and 2, we ran,

N. 89° 36' E. between the North and South halves of the S.W. quarter of section 2.

13+18.6 Set a 3/4"X 30" iron pin for the center of the S.W. 1/4 of the section, with 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

26+57.2 The South 1/16 corner on the N.& S. centerline of the section, previously described.

Thence N. 89° 31 1/2' E. between the North and South halves of the S.E. quarter of section 2.

13+24.8 ~~52+82.0~~ Set a 3/4"X 30" iron pin for the center of the S.E. quarter of the section, with a 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

26+49.6 The South 1/16 corner on the line between sections 2 and 1, previously described.

Returning to the corner to sections 3-3-4 on the Twp. line, we ran Southerly by traverse between sections 4 and 3. Not finding any trace of the quarter corner, we proceeded to the corner to sections 4-3-9-10, where we found a stone with 5 notches on the South and 3 notches on the East corners, also remnants of 3 bearing trees. Leaving the stone undisturbed, we set a 2"X 48" galv. iron pipe at a point 0.5 ft. North and 0.2 ft. East of the high point of the rock. The pipe has a brass cap on which is stamped a cross and the numbers 4-3-9-10 and, circumferentially, SEC. COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled SEC. COR. on 2 faces in black, and marked 4 new bearing trees, as follows: