

Cour Surveyor's Record, Tillamook Cour Oregon

240

T 4 S, R 10 W.

Rewitnessed Corners

Mervin Whitmore, U.S. Forest Service

<p>XXXXX/</p> <p>Sec. Cor.</p> <p><u>26</u> 35</p>	<p>Set a fir limb for corner post from which A 36" dead fir snag bears N 58°W 43 lks. dist. mkd. $\frac{1}{4}$ in bark (old BT) An 14" alder bears S 88°E 7$\frac{1}{2}$ ft. dist. mkd. $\frac{1}{4}$S35BT scribed in bark (new BT).</p> <p>In the presence of Willis Horner and Harold Nicholson. Feb. 18, 1954.</p>
<p>Sec. Cor.</p> <p><u>10</u> 15</p>	<p>Set an iron pipe 1$\frac{1}{4}$", 4 ft. long & 2 ft. in ground, from which A 54" dead fir snag bears S 16°E 48 ft. slope dist. The original scribing was not legible. Remarked this tree $\frac{1}{4}$S15BT. Remains of a fir stump about 14" diam. bears N 56°E 43$\frac{1}{2}$ ft. dist. slope dist. All scribing rotted off. A 30" fir with a 6-pronged top bears N 42°E 36 ft. slope dist. mkd. $\frac{1}{4}$S10BT (new BT).</p> <p>In the presence of Willis Horner, Tom Paterson, and Allen Taylor. April 20, 1955.</p>
<p>Book I</p> <p>240</p>	<p>240</p>