CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 5, 6, 7 and 8, T. 2N, R.6W, W.M., Tillamook and Washington Counties, Oregon.

OR IGINAL

Post (now missing, found recently scribed post in place) from which a:

24" Fir bears N32°E 41 1ks.; now 26" snag, face unexposed. 24" Fir bears S802°E 27 lks.; now 26" stump, scribe 8 remaining on upper face, lower face unexposed.
24" Fir bears S20°W 40 lks.; now 27" stump, lower face

remaining unexposed.

36" Larch bears N60°W 4.5 lks.; now 39" snag, scribe R visible, rest unexposed.

RESTORED

Var. 2120

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T2N R6W S5 S6 S7 S8 1956 RS 359," 26 inches in ground, in small mound of stone, and from which:

5" Fir bears Sll°W 20.9 ft.; scribed T2N R6W S7 BT RS 359

5" Fir bears N37°E 6.1 ft.; scribed T2N R6W S5 BT

5" Fir bears N85°W 14.5 ft.; scribed T2N R6W S6 BT

5" Fir bears S65°E 25.2 ft.; scribed T2N R6W S8 BT

Oregon State Board of Forestry metal location poster on 5" Fir BT S65°E. Crown Zellerbach tag on 36" Larch.

Dated June 15, 1956

Restored by Richard A. Morris, Transitman

_ under my direction.

REGISTERED OREGON LAND SURVEYOR

ARNOLD G. GIBSON 359

Present and witnessed by Robert Sturm

Book I

262