CHAINS

RESTORED CORNER FOR CREGON STATE BOARD OF FORESTRY

Closing Section corner common to Sections 30 and 31, T. 3N, R. 6W, W.M., Washington and Tillamook Counties, Oregon.

ORIGINAL

Post (now missing) from which a:

48" Fir bears N22°E 68 lks.; now 40" stump, scribes BT remaining, rest cut off when logged.

60" Fir bears S35°E 30 lks.; now 54" stump, scribe W remaining, rest burnt out.

8" Hemlock bears S28°W  $30\frac{1}{2}$  lks.; now missing, point falls in slide area.

RESTORED

Var. 2120E

Set  $1\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T3N R7W R6W S25 S30 S31 CC 1957 RS401," 34 inches in ground, in mound of stone, and from which a:

5" Fir bears S45°E 44.2 ft.; scribed T3N R6W S31 CC BT.
7" double top Fir bears N18°E 83.4 ft.; scribed T3N R6W S30 CC BT RS401.

Oregon State Board of Forestry metal location poster on 5" Fir BT. Set 4" x 4" x 60" white painted Cedar post 0.8' West of pipe.

Dated October 25, 1957

Restored by

REGISTERED OREGON LAND SURVEYOR

Richard A. Morris

Present and witnessed by Robert Sturm

Book I