

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)

West One Sixteenth corner common to Sections 27 and
34, T2S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 3/4" x 36" galvanized iron pipe with 2" bronze cap marked "W 1/16
S27 S34 1957 RS401", 12 inches in ground, in mound of stone 24"
high, and from which a:

35" Hemlock bears S55 1/8 E 44.5 ft.; scribed W 1/16 S34 BT.

31" Hemlock bears N18 1/2 E 31.2 ft.; scribed W 1/16 S27 BT RS401.

Oregon State Board of Forestry metal location poster on 35" Hemlock BT.
Set 4" x 4" x 56" white painted Cedar post 1.2 ft. S. W. of pipe.
Corner point falls in 36" creek course N10W.

North One Sixteenth corner common to Sections 33 and
34, T2S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 3/4" x 36" galvanized iron pipe with 2" bronze cap marked "N 1/16
S33 S34 1959 RS401", 32 inches in ground, in mound of stone, and
from which a:


15" Hemlock bears S85 E 114.9 ft.; scribed N 1/16 S34 BT RS401.

34" Spruce bears N7 1/2 W 109.8 ft.; scribed N 1/16 S33 BT.


Oregon State Board of Forestry metal location poster on 34" BT.
Set 4" x 4" x 56" white painted Cedar post 1.0' N.W. of pipe.

Dated April 14, 1959

Established by



Richard A. Morris



Present and witnessed by H. Russell
R. Cop