CHAINS

ESTABLISHED CORNERS FOR STATE OF OREGON-DEPARTMENT OF FORESTRY (See official plat)

North One-sixteenth corner common to Sections 8 and 9, TIS, RSW, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 212E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N 1/16 S8 S9 1962 RS401", 30 inches in ground, and from which a:

10" Hemlock bears N292W 2.8 ft.; scribed N 1/16 S8 BT RS401. 8" Hemlock bears S47E 8.8 ft.; scribed N 1/16 S9 BT.

Corner is 40° North of power line.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. NW of corner pipe.

Oregon State Forestry Department metal location poster on 10" Hemlock BT.

Northeast One-sixteenth corner for Section 8, TIS, RSW, W.M., Tillamook County, Oregon.

* * * * * * * * *

ESTABLISHED

Var. 212E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY NE 1/16 S8 1962 RS401", 32 inches in ground, and from which a:

4" Hemlock bears S65E 4.6 ft.; scribed NE 1/16 S8 BT. 6" Hemlock bears N73W 15.2 ft.; scribed NE 1/16 S8 BT RS401.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. SW of corner pipe.
Oregon State Forestry Department metal location poster on 4" Hemlock BT.

Dated June 27, 1962

Established by _

under my direction.

B. Davis, Transitman

Present and witnessed by D. Fletcher C. Curl

REGISTERED O R E G O N LAND SURVEYOR

Richard A. Morris

401

478

Book I