



UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
710 N. E. Holladay
Portland 12, Oregon
Survey Records Office

IN REPLY REFER TO:

100.4a
6100

February 28, 1962

County Surveyor
Yamhill County
McMinnville, Oregon

Gentlemen:

The following has been added to the record files of this office:

- Survey
- Dependent Resurvey
- Subdivision
- Supplemental Plat

Section _____, T. 4 S, R. 7 W, Will. Mer.,
1 Plat, 86 Pages Notes, Dated 12/8/62

There is attached:

- 2 Copy of each plat
- The triplicate copy of the field notes

Notes may be copied for \$12.25

Very truly yours,

Thomas A. Tillman
Chief, Branch of Cadastral Engineers
By

H. June Morse
H. June Morse, Clerk

Enclosures

Copy to: State Land Board - with enclosure (Plat)
State Tax Commission - with enclosure (Plat)
U. S. Forest Service - with enclosure (2 Plats)
Tillamook County - 2 copies

Book I

504

Sec. 14, 15, 19, 20, 21, 22, 23, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, Data Available, See Map - A 1042 -

Township 1 North, Range 9 West

Section corner 8/9 T1N, R9W. Found 2 BTs with scribe. Set 4 hemlock
17 16
post and drove iron pipe for corner and referenced as follows:

12" fir N22°W 7.4' S8BT Yellow tag
10 hemlock N52°E 22.2' S9BT Yellow tag
7" hemlock South 3.9' S16BT
10" fir S51°W 33.0 S17BT

Var. 20°E
March 16, 1960

Scribed by: W. E. Jordan, LFCo.
Witness: Dave Bowden, Robt. Stewart,
Jack Willford

1/4 corner 8/9 T1N, R9W. Set iron pipe for corner and referenced as follows:

18" cedar N42°E 28.0' 1/4S9BT
24" cedar N20°E 24.3' 1/4S9BT

Corner sets on east slope between road to west and cat road east and
Kilchis River 200 ft. east and creek prox. 165' south of corner

Var. 21°30'
July 5, 1960

Scribed by: W. Jordan, LFCo.
Witness: D. Bowden

North 1/16 corner 8/9 T1N, R9W. Set iron pipe for corner and referenced as
follows:

30" hemlock N20°W 20.7' N 1/16 S 8 B.T. Yellow tag
17" alder N16°E 3.5' N 1/16 S 9 B.T. Yellow tag

Corner sets 60' south of a sharp draw.

Var. 21°30'
July 6, 1960

Scribed by: W. Jordan, LFCo.
Witness: D. Bowden

East 1/16 corner 5/8 T1N, R9W. Set iron pipe for corner and referenced as
follows:

30" hemlock S20°E 37.0' E 1/16 S 8 B.T. Yellow tag
30" hemlock N50°W 3.3' E 1/16 S 5 B.T. Yellow tag

Corner on NE slope and just north and west of end of a cat road.

Var. 21°30'
July 6, 1960

Scribed by: W. Jordan, LFCo.
Witness: D. Bowden

1/4 corner 5/8 T1N, R9W. Set iron pipe for corner and referenced as follows:

16" fir N7°E 27.8' 1/385B.T. Yellow tag.
12" fir N80°E 21.0' 1/485B.T. Yellow tag.

Cat road ends 100' north of corner.
Corner on 60% south slope
Rock face south of corner

Var. 21°30'
July 5, 1960

Scribed by: W. Jordan, LFCo.
Witness: D. Bowden

Book I

504

Book I