

County Surveyor's Record, Tillamook County, Oregon

T4SR9W

Rewitnessed corners

Leonard Whitmore, U.S. Forest Service

Sec. Cor. The original stone with 4 grooves on south & 3 grooves
 9 10 on east faces.
 15 15 18 in. fir, S. 7°E., 21½ ft. mkd. T4SR9WS15BT (new BT)
 16 in. fir, N. 57°E., 21½ ft. mkd. T4SR9WS10BT (new BT)
 12 in. fir, N. 27° 30' W., 55½ ft. mkd. T4SR9WS9 BT (new BT)
 16 in. fir, S. 56°W., 30 ft. mkd. T4SR9WS16BT

In presence of Mervin Whitmore, January 29, 1961

¼ Cor. Original post with visible scribing 4S
 10 14 in. fir, N. 61° 30'E., 11½ ft. mkd ¼ S 10 BT (new BT)
 15 12 in. fir, S. 39°W., 12 ft. mkd ¼ S 15BT (new BT)

In presence of Mervin Whitmore, January 7, 1961

Sec. Cor. Original rock mound for corner
 14 13 16 in. fir, S. 62°W., 13 ft. mkd. T4SR9WS23BT (new BT)
 18 in. fir, N. 8°W., 24 ft. mkd. T4SR9WS14BT (new BT)
 23 24 18 in. fir, N. 54°E., 42 ft. mkd. T4SR9WS13BT (new BT)
 18 in. fir S. 58°E., 23 ft. mkd. T4SR9WS24BT (new BT)

In presence of Mervin Whitmore, January 7, 1961

¼ Cor. Original post with visible mks. ¼ 22 on N. & 27 on S. side.
 22 20 in. forked top fir, S. 4°W., 33ft. mkd. ¼ S27BT (new BT)
 27 14 in. fir, N. 14°E., 20½ ft. mkd. ¼ S22BT (new BT)

In the presence of Mervin Whitmore, February 11, 1961

Sec. Cor.
 10 11 Set a 3"x3"x 24" spruce limb mkd. S 10 on N.W., S11 on N.E.,
 15 14 S14 on S.E., and S 15 on S.W. faces. Placed 3 stones at
 base of post.
 24" alder N. 59° 45' E., 28 ft. (original BT)
 24" alder N. 13° 40' W., 78 ft. (original BT)
 18 in. alder S. 61° 15' W., 30 ft. (original BT)
 16 in. alder S. 58° 15' E., 36 ft. (original BT)

By Mervin Whitmore February 8, 1961

21 22 Closing corner for secs. 21-22 SOUTH BOUNDARY
 Original corner stone mkd. S. 21 on W. and S 22 on east faces
 12 in. fir, N. 85° W., 41 ft. mkd, S 21 BT (new BT)
 14 in. fir, N. 35½E., 42½ ft mkd. S22 BT (new BT)

In presence of Mervin Whitmore, February 11, 1961

Pg. 1 of 5 M. Whitmore