

CHAINS
FEET

A hemlock stump, 12" in diameter, rotted and burned off just above ground level, with the trunk of the tree lying by it with a 4" X 8" blazed face and 3" X 6" blaze above this of some age, bears S 30° W, a distance of 19.1 feet. No scribes visible.

No evidence could be found of the fir or vinemaple bearing trees.

(The 24" hemlock bearing tree was tested for the bearing trees of the CC of Sections 22 & 27 and no trees were found to agree with such a setting.)

At the corner point

Set a 1½" iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped:

T 2N, R 6W S 27 S 23 S 26 1949 199

from which:

A fir stump, 40" in diameter, bears S 11° E, 82.1 feet, scribed T 2N, R 6W S 26 199

A fir tree, 4" in diameter, bears N 27° E, 17.4 feet, scribed S 23

A metal location poster on a fir stump, 38" in diameter, bears S 21° W, a distance of 55.4 feet.

No evidence found of the closing corner to sections 22 & 27 therefore re-establish the closing corner to sections 22 & 27 on the West line of Section 23 by chaining North a distance of 81.8 feet from the Cor. of section 23 & 26 as called for in original survey.

At point for CC corner

Set a 1½" iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped:

T 2N, CC S 22 S 27 S 23 R 6W 1950 199.

from which:

A fir stump, 36" in diameter, bears N 21° E, a distance of 36.1 feet, scribed S 22 199.

A fir tree, 3" in diameter, bears S 21° W, a distance of 7.5 feet, scribed S 27.

A metal location poster on a fir stump, 37" in diameter, bears S 76° W, a distance of 15 feet, marked: Sec. 27
T 2N, R 6W CC 22/27 15 feet N 76° E.

Adjustment of temp stakes to true line position and establishment of monuments by proportional measurement.