

CHAINS	
	From the corner to secs. 3, 4, 9, & 10.
	N 89° 15' <sup>W?</sup> on a random line bet. secs. 4 & 9.
455.7	East edge of Wilson River, 74 feet wide, course South.
586.6	East edge of North Fork of Wilson River 60 feet wide, course South.
1318.6	Spur, sloping south. Set temporary stake.
2573.4	Set temporary stake.
3456.0	Stream, 2 feet wide, course South.
3886.4	Set temporary stake.
4637.3	Stream, 2 feet wide, course S 15° E.
5048.0	Stream, 2 feet wide, course S 20° W.
5237.9	Corner to sections 4, 5, 8, & 9 bears N 63° 35' W, a distance of 97.4 feet.
	Adjustment to true line & setting of monuments.
	Relative to the calculated bearing of the random line (N 89° 15' W) the true line between sections 4 & 9 bears N 88° 48' W, a distance of 5325.8 feet,
0	The corner to sections 3, 4, 9, & 10.
1331.4	Point for E 1/16 corner between sections 4 & 9 by proportionate distance. Adjustment from temporary stake 1318.6 -- North 10.7 feet, West 12.7 feet.
	At the point for corner
	Set a 1½ inch iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: E 1/16 S 4 S 9 1950 199.
	from which:
	A fir stub, 24 inches in diam., bears S 89° W, a distance of 63.9 feet, scribed: S 9 E 1/16 199.
	Placed a metal location poster on a 21 inch fir stub & marked it: Sec 9 T1N R7W E 1/16 4/9 Cor 17.6 Ft N 17° E.
2662.9	Point for ¼ corner between sections 4 & 9 by proportionate distance. Adjustment from temporary stake 2573.4 -- North 22.3 feet, West 89.1 feet.
	At the point for corner
	Set a 1½ inch iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: ¼ S4 S9 1950 199.
	from which:
	A willow, 10 inches in diam., bears S 35° W, a distance of 20.4 ft., scribed: ¼ S9 199.