

CHAINS

RESTORED CORNER FOR THE OREGON STATE BOARD OF FORESTRY

November 15, 1951

One quarter corner between sections 1 & 6, Township 2 South, Ranges 6 & 7 West, W. M., Tillamook County, Oregon.

The point for corner determined by a:

2" x 2" stake set in place of a stake set in 1949 S80E 25.1 ft. (38 lks) from a 30" Hemlock snag; scribe marks then visable. Snag, since burnt out. No evidence of other BT found.

At the point for corner

Set a 1 1/2" x 36" galvanized iron pipe 3 ft. long with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S1 S6 1951 142" 2 1/2 ft. in ground from which a:


32" Fir stub bears N28W 17.3 ft.; scribed 1/4 S1 BT 142.  
53" Fir stump bears S42E 6.2 ft.; scribed 1/4 S6 BT 142.  
(Distances measured from center of bearing trees).

Nailed a metal location poster on the 32" fir stub BT & marked it: Sec 1 T2S R7W 1/4 cor 16.3 ft. S26 1/2 E.



Restored by

*Walter M. Robertson*



Walter M. Robertson

Present & Witnessed by *Don Davis*  
Don Davis Asst. Forest Engineer OSBF

Present & Witnessed by *Richard Morris*  
Richard Morris Chairman OSBF

Present & Witnessed by *Leonard Koster*  
Leonard Koster

Present & Witnessed by *Webb Howell*  
Webb Howell