

## BOUNDARY SURVEYS

## SECTIONS 17 &amp; 18, T2N, R6W, W.M.

NOTE 1: May 15, 1957, With Rob't J. McCullough, at the corner to sections 7, 8, 17 & 18, T2N, R6W, W.M., I find original BT's as follows:

A fir stump 36" diameter bears N 67° E 23.0 feet, the blaze scars very prominent. I do not chop them out.

A hemlock stump 18" diameter bears S 47° E 14.5 feet. A portion of the letter "R", the figure "6", and a portion of the letters "BT" are visible.

A hemlock stump 16" diameter bears N 47° W 35.6 feet. The blazes are prominent, but the faces are rotted out and no scribing is visible.

A remnant of a small hemlock stump bears S 9° W 7.0 ft.

For the corner I set a 1 1/2" galvanized iron pipe 30" long 10" in the ground in a notch cut in the side of a log.

NOTE 2: At the 1/4 corner between sections 8 & 17, T2N, R6W, W.M. I find a galvanized iron pipe set by this surveyor in 1956 (see Note 6 of Survey to Isolate NE 1/4 of S8, T2N, R6W, August--December, 1956)

NOTE 3: For the 1/4 corner between sections 17 & 18, T2N, R6W, I set a 1 1/2" diameter galvanized iron pipe 30" long 20" in a mound of stones from which:

A fir snag 30" diameter bears S 82° W 5.6 feet marked 1/2 S BT S18 322.

A fir stump 30" diameter bears N 11° E 32.8 feet marked 1/2 S BT.

This point is on the top of a narrow rocky ridge, course E-W which ends in a bluff 20 feet west of the corner. It is 100 feet north of a spring branch filled with rubble from logging.

NOTE 4: May 24, 1957, at the intersection of the center-lines of section 17, T2N, R6W, W.M. I set a 1 1/2" galvanized iron pipe 30" long 24" in the ground, from which:

A hemlock 14" diameter bears N 52° E 74.3 feet marked C 1/2 1957 322 BT.

There are no trees west of the corner large enough to bear a mark.

NOTE 5: May 9, 1957, at the 1/4 corner between sections 16 & 17, T2N, R6W, W.M. I find the original stone marked 1/4. Beside it I find a scribed post 4" x 6" x 4" tall and a galvanized iron pipe bearing an Oregon State Board of Forestry brass cap from which original BT's bear as follows:

A fir stump 42" diameter bears S 80° W (not SE as given in the notes furnished me) 9.7 feet marked 1 S, the balance of the scribing not being chopped clear.

A fir stump 42" diameter bears N 50° E 12.5 feet bearing a scar which has not been chopped out.

An additional BT stump NW was scribed 1/4 S17 BT 199.