

Cour Surveyor's Record, Tillamook Cour Oregon

T 5 S R 9 W.

Rewitnessed corners

Mervin Whitmore, U.S. Forest Service

| | | |
|--------------------------------------|--|--|
| <p>CHAINS 34 35</p> | <p>Set 3/4" pipe for cor. on 1st Stan. Par. S. A 12" fir, N.34°W. 25ft. mkd. T5SR9WS34 BT. (New BT) A 24" fir, N.80°E. 50 1/2 ft. mkd. T5SR9WS35BT. (New BT) In the presence of Max Carver Oct. 24, 1958</p> <p>5.5.9</p> | |
| <p>1/4 Cor 33 34</p> | <p>Set iron pipe 6" high for cor. A 22" alder N. 47°E. 20 1/2 ft. mkd. 1/4S34BT. A 20" alder marked 1/4S CSBT (by a previous survey) bears N.50°W.6 ft. In the presence of Ken Drahos and Max Carver. Oct. 14, 1958</p> <p>5.5.9</p> | |
| <p>1/4 Cor 27 34</p> | <p>Set iron pipe. A 22" hemlock, N. 29°E. 41 ft. mkd. 1/4S27BT. (New BT) Old alder tree, N.80°W. 23 ft., (Old BT) In the presence of Max Carver and DeWayne Seufert. Oct. 28, 1958</p> <p>5.5.9</p> | |
| <p>1/4 Cor S. bdy. 34</p> | <p>Set iron pipe alongside of fir limb post An 18" fir, N.35°30' W. 35 1/2 ft. mkd. 1/4S34BT. (New BT) A 20" fir, N. 64°E. 47 1/2 ft. mkd. 1/4S34BT. (New BT) In the presence of Max Carver & DeWayne Seufert Oct. 27, 1958</p> <p>5.5.9</p> | |
| <p>Sec 1 6 12 7</p> | <p>T 5 S Rgs. 9 & 10 W. Set a fir limb post. A 12" dead fir stub cut off above old marks bears N.73°E. 11 lks. with scribe marks visible but not legible (Old BT) A 10" dead fir stub cut off above old ax marks bears S. 53°E. 40 lks. (Old BT) A 10" dead fir stub cut off above old ax marks bears S.80°W. 17 lks. (Old BT) The original NW. BT is gone. A 48" dead fir snag N. 23°30'W. 30 ft. mkd. T5SR10WS1BT. (New BT) A 19" fir, N. 28°E. 20 ft. mkd. T5SR9WS6BT. (New BT) A 28" fir, S.31°30'E. 34 1/2 Ft. mkd. T5SR9WS7BT. (New BT) A 23" fir, S.41°W. 24 ft. mkd. T5SR10WS12BT. (New BT) In the presence of Mark Shultz and Max Carver. Sept. 9, 1957.</p> <p>5.5.9</p> | |
| | <p>(5.5.9)</p> | |