

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

South West One Sixteenth corner for Section 11, T1N, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SW 1/16 S11 1959 RS401", 34 inches in ground, and from which a:

- 12" Hemlock bears S87W 7.9 ft.; scribed SW 1/16 S11 BT.
- 15" Hemlock bears N45E 4.6 Ft.; scribed SW 1/16 S11 BT RS401.

Oregon State Board of Forestry metal location poster on 9" Hemlock N18W 1.0'.

Set 4" x 4" x 60" white painted Cedar post 1.0' S.E. of corner pipe.

-----

North One Sixteenth corner common to Sections 11 and 12, T1N, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N 1/16 S11 S12 1959 RS401", 34 inches in ground, in mound of stone, and from which a:

- 26" Hemlock bears S25W 47.9 ft.; scribed N 1/16 S11 BT (by Longview Fibre Co.)
- 18" Hemlock bears N32 $\frac{1}{2}$ E 195.5 ft.; scribed N 1/16 S12 BT RS401.
- 3/4" Iron pipe bears N24 $^{\circ}$ 27'E 2.4 ft.; previously set by Longview Fibre Co.


Oregon State Board of Forestry metal location poster on 26" Hemlock BT.

Set 4" x 4" x 60" white painted Cedar post 1.0' S.W. of 1 $\frac{1}{2}$ " corner pipe.

Center line of road (N10E and S15E) bears East 24.0 ft.

Dated December 31, 1959

Established by



*Richard A. Morris*  
MAY 10. 1957  
Richard A. Morris  
401

Present and witnessed by H. Russell  
R. Cop  
E. Nylund