

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)
Southwest One-sixteenth corner for Section 2, T1N,
R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SW 1/16 S2 1960 RS401", 26 inches in ground, in mound of rock, and from which a:

- 15" Hemlock bears S84E 26.4 ft.; scribed SW 1/16 S2 BT.
- 15" Hemlock bears N46W 18.2 ft.; scribed SW 1/16 S2 BT RS401.

Set 4" x 4" x 52" white painted Cedar post 1.4 ft. West of corner pipe.
Oregon State Board of Forestry metal location poster on 15" Hemlock BT N46W.

* * * * *

South One-sixteenth corner common to Sections 3 and 2, T1N, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S 1/16 S3 S2 1960 RS401", 34 inches in ground, and from which a:

- 40" Hemlock bears S87W 58.2 ft.; scribed S 1/16 S3 BT.
- 28" Hemlock bears N89E 75.3 ft.; scribed S 1/16 S2 BT RS401.
- 6" Creek course S5E, East 31.7 ft.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. SE of corner pipe.
Oregon State Board of Forestry metal location poster on 40" Hemlock BT.

Dated February 27, 1960

Established by Harold J. Russell under my direction.
Harold Russell, Engineering Tech. I

Present and witnessed by R. Cop
E. Nylund

