

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 9, 10, 15 and 16, T3S, R8W, W.M., Tillamook County, Oregon.

ORIGINAL

Basalt stone 20" x 8" x 5" (now 6" x 7" x 10", 4 notches visible, down hill out of place with 3/4" x 5" pipe beside it) from which a:

- 4" Alder bears S41W 32 lks.; now missing.
- 4" Alder bears S51 1/4 E 78 lks.; now missing.
- 12" Fir bears N49 1/2 E 204 lks.; now 36" face unexposed, outline of face visible in bark.
- 24" Fir bears N89 1/2 W 133 lks.; now missing.

RESTORED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S9 S10 S16 S15 1961 RS401", in correct position according to Fir BT, over top of 3/4" I. P., with remainder of original stone alongside, and from which a:

- 17" Fir bears S28 1/2 W 27.3 ft.; scribed T3S R8W S16 BT RS401.
- 27" Fir bears N84W 65.1 ft.; scribed T3S R8W S9 BT.
- 13" Fir bears S18E 25.2 ft.; scribed T3S R8W S15 BT.

Above Original 12" Fir bears N49 1/2 E 134.6 ft.; scribed BT.

Oregon State Board of Forestry metal location poster on 13" Fir BT.  
Set 4" x 4" x 52" white painted Cedar post 1.0' N.W. of pipe.  
Set original corner stone alongside pipe.

Dated July 28, 1961

Restored by



*Richard A. Morris*  
MAY 10. 1957  
Richard A. Morris  
401

Present and witnessed by H. Russell  
E. Nylund  
A. Duncan