

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)

North-South 1/64 corner common to Sections 11 and 12 (N.W. cor. SW $\frac{1}{4}$, SW $\frac{1}{4}$, NW $\frac{1}{4}$, Sec. 12) T.1 S, R. 8 W, W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N-S 1/64 S11 S12 1960 RS401", 33 inches in ground, and from which a:

22" Hem. bears S46 $\frac{1}{2}$ E 40.8 ft.; scribed N-S 1/64 S12 BTRS401;
15" Hem. bears N37W 61.9 ft.; scribed N-S 1/64 S11 BT;

Set 4" x 4" x 54" white painted Cedar post 0.6 ft. N.W. of corner pipe. Oregon State Board of Forestry metal location poster on 22" Hem. BT;

Present and witnessed H. Russell, R. Cop, E. Nylund, J. Sehorn.

Witness corner for the one quarter corner common to Sections 12 and 13 T. 1 S, R. 8 W, W.M., Tillamook County, Oregon

ESTABLISHED

Set at a point on the section line N88° 28' 04" E 20.6' from the $\frac{1}{4}$ corner point in a rock cliff, 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY WC $\frac{1}{4}$ S12 S13 1960 RS401", 34 inches in ground, in mound of rock, and from which a:

14" Hem. bears N37E 68.7 ft.; scribed W.C. $\frac{1}{4}$ S12 BTRS401;
Base of rock cliff bears N72W 77.6 ft.; scribed W.C. B.O.

Set 4" x 4" x 60" white painted Fir post 2.0 ft. West of corner pipe. Oregon State Board of Forestry metal location poster on 14" Hem. BT; corner pipe sets on S. edge of old road.

Dated March 31, 1961

Established by

Present and witnessed by R. Cop, M. Trout



Richard A. Morris
MAY 10, 1957
Richard A. Morris
401