

List of Corners Found and Set in Section 19, Township 1 North, Range 9 West, W.M., Tillamook County, Oregon, Garibaldi Tract

Refer to Survey Map dated May 20, 1965, Longview Fibre Company Map No. 469

Closed traverse survey was made all areas with transit and tape with vertical angles measured with transit and tape read to nearest .1 foot. SE Section corner Section 19 was reestablished by double proportionate measurement, other corners established by single proportionate measurement. Lost corners were all searched for very thoroughly.

18 ¼ corner between Sec. 18 and 19, T1N, R9W, reestablished.
19 Drove a ½" x 30" I. pipe on bank 32 feet north of Moss Creek, from which:

A 26" Hemlock bears N 20° W 89.00' L. W. yellow tag
A 7" Alder bears S 73° W 30.00' L. W. yellow tag

Corner is 200 feet South of logging road near road jct.

Scribed by R. B. Bass
Witnesses: R. Stewart
 T. Budge 5-5-65

Center ¼ Sec. 19, T1N, R9W established.
Drove a ½" x 30" I. pipe on steep north slope from which:

A 16" Hemlock bears due north 8.37' L.W. yellow tag
An 18" Hemlock bears S 74° E 10.90' L.W. yellow tag

Corner is 260' west of main fork Moss Creek and 134' south of Side Crk.

Scribed by R. G. Bass
Witnesses: R. Stewart
 T. Budge 5-3-65

C-E 1/16 Sec. 19, T1N, R9W established.
4 tallies west of 1/4 corner between Sec. 19 and 20
Drove a 1/2" x 30" I. pipe from which:

A 20" fir bears N 35° W 11.27' L.W. yellow tag
A 20" fir bears S 36° E 7.08' L.W. yellow tag

Corner on moderate west slope.

Scribed by R. B. Bass
Witnesses: R. Stewart
 T. Budge 5-6-65

19/20 East 1/4 corner Sec. 19 between Sec. 19 and 20, T1N, R9W reestablished.
Drove a 1/2" x 30" I. pipe 36' south of edge of cliff from which:

A 3" fir bears N 84° W 7.37 L.W. yellow tag
A 9" W.R.C. bears N 72° E 9.33 L.W. yellow tag

Very steep west slope.

Scribed by R. B. Bass
Witness: R. Stewart
 T. Budge 5-6-65