

(45)

CHAINS
FEET

SURVEY OF SECTION LINE BETWEEN SECTIONS 13 & 24 T1N R6W WM.

RETRACEMENT:

Beginning at the temp. stake, set on retracement of the line North from the corner to Sections 24, 25, 19 & 30 from which the reestablished corner to Sections 13, 24, 18 & 19 bears South 19.2 ft. and East 25.4 ft.

Starting with a compass bearing, variation 22° E, using a K & E Light Mtn Transit West on a random line between Sections 13 & 24.

Random
line
Dist. feet

1242	Road running N 10° E and S 20° W.
1324.6	Set temp. stake.
1705	Ridge bears North and South.
2649.2	Set temp. stake.
5298.4	The corner to Secs. 13, 14, 23 & 24, determined on the retracement between Secs. 23 & 24, bears N 51° E adistance of 74.2 ft.
	Adjustment of temp. stakes to true line positions and establishment of monuments.
	Relative to the compass bearing of the random line, the true line from the corner of Secs. 13, 24, 18 & 19 to the corner of Secs. 13, 14, 23, 24 bears N 89° 17' W.
1316.6	Point for E 1/16 corner bet. Secs. 13 & 24 Adjustment from temp. stake South 2.8 ft. East 33.4 ft. Set an iron pipe, 1½ inches in diam. 3 ft. long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped E 1/16 S13, S24, 1949, 199. Placed a mound of stone around corner. General location of corner is on a flat spot above and west of the cut bank of road.
2633.3	Point for 1/4 corner bet. Secs. 13 & 24 Adjustment from temp. stake N 13.7 ft. East 41.6 ft.

(Continued on page 46)