

Survey for Oregon State Board of Forestry.

Section line between Sections 6 & 7, Township 1 North, Range 5 West, W.M., Tillamook County, Oregon

RETRACEMENT:

Beginning at a temporary stake, previously set by a random line West between Sections 5 & 8, from which the corner to Sections 5, 6, 7, & 8, Township 1 North, Range 5 West, bears North $13^{\circ} 48'$ East, a distance of 59.4 feet determined by a $1\frac{1}{2}$ inch iron pipe with Oregon State Board of Forestry bronze cap stamped T 1N, R 5W, S 6 S 5 S 7 S 8, 1949, 199, which I had previously set to restore the monument. Variation 22° East, using a K & E Light Mtn. Transit.

West on a random line between Sections 6 & 7, Township 1 North, Range 5 West, W.M.

2636.0 Set temp stake. Find no evidence of $1/4$ corner

2830 Road running North and South

3672 Stream 4 ft. wide, course SE

4675 Cat road running North and South

5233.8 The corner to Sections 6, 7, 1 & 12, Township 1 North, Ranges 5 & 6 West bears North $35^{\circ} 36'$ East, a distance of 136.0 feet. Corner determined by a $1\frac{1}{2}$ inch iron pipe with an Oregon State Board of Forestry bronze cap stamped T 1N, S1 S 6 S 12 S 7 R 6W R 5W 1949, 199, which I had previously re-established.

Adjustment of temporary stakes to true line position and establishment of monuments.

Relative to the compass bearing of the random line the true line between Sections 6 & 7 bears North $89^{\circ} 25'$ West, a distance of 5169.1 feet

2605.4 Point for $1/4$ corner between sections 6 & 7 by single proportionate measurement.

Adjustment from temp. stake 2636.0 - North 84.4 feet East 45.0 feet.

Set a $1\frac{1}{2}$ inch iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped $1/4$ S 6 S 7 1950, 199

from which:

A fir stump, 42 inches in diameter, bears North 32° West, a distance of 22.7 feet. Scribed $1/4$ S 7 199

A fir tree 3 inches in diameter bears South $25^{\circ} 30'$ West, a distance of 74.0 feet. Scribed $1/4$ S 7