## SURVEY FOR THE OREGON STATE BOARD OF FORESTRY

## April 11, 1950

Restoration of the monument to the corner common to Sections 11-12-13 & 14, Township 1 North, Range 6 West, Willamette Meridian, Tillamook County, Oregon.

The point for the corner determined by remains of the original bearing trees:

- A hemlock stump, 14 inches in diameter, bears S 62° E a distance of 25.7 feet (39 lks.). The scribe marks BT are plainly visible.
- A hemlock stump, 16 inches in diameter, bears N 17° E a distance of 31.2 feet (47 lks.). The scribe mark T is plainly visible.

No evidence remains of the other bearing trees.

At the point for corner:

Set a  $1\frac{1}{2}$  inch iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped:

T lN, R 6W, S 11 S 12 S 14 S 13 1950 199

## from which:

- A fir stump, 5 feet high, 64 inches in diameter, bears S 23°15' E a distance of 45 feet, scribed: T lN, S 13 199.
- A cross (‡), 7 inches x 7 inches, chiseled on the top of a flat-topped round boulder, 30 inches in diameter, 16 inches above ground, bears S 24°45° W, a distance of 10.0 feet.

Placed a mound of stone around the corner pipe. Placed a metal location poster on the 64 inch stump BT.

Present:

Lyle E. Beyers Don Davis Lyle E. Beyers Forest Engineer



BOOK 2