

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Quarter corner common to section 6, T. 1 N., R. 6 W., W. M.,
Tillamook County, Oregon.

Point for corner determined by the remains of bearing tree as describ-
ed by notes in the Tillamook County Surveyors Office dated Feb-
ruary 4, 1943:

30" Fir bears S84E 11.0 ft. found and rescribed; now a
30" Fir stump with scribe marks visible on burnt face.

At the point for corner

Set a 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked
"OREGON STATE BOARD OF FORESTRY 1/4 S6 1949 199", 2 1/2 ft. in
ground. Raised mound of stone around pipe from which a:

39" Fir snag bears East 49.0 ft.; scribed 1/4 S6 199 BT.

Placed an Oregon State Board of Forestry metal location poster
on 30" Fir stump BT and marked it: Sec 1 T1N R7W 1/4 Cor
11.0 ft. N84W.

Dated June 8, 1951.

This corner was restored by Don D. Davis
Don D. Davis Asst. Forest Engineer
under my direction.

Lyle E. Beyers

Present and witnessed by Richard A. Morris
Richard A. Morris Compassman

Present and witnessed by Douglas Stafford Chainman