

(92)

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Corner common to sections 13, 14, 23 and 24, T. 2 S., R. 7 W., W.M., Tillamook County, Oregon.

ORIGINAL

Post, now missing, from which a:

- 60" Fir bears S24E 51 lks; now a 60" stump, scribe marks BT exposed on a badly burned face.
- 70" Fir bears N43E 43 lks; now a 4 ft. stump N40E 10 lks, scribe marks BT barely visible on burnt face.
- 60" Fir bears N40W 10 lks; now a 60" stump N45W 43 lks, badly burnt.
- 28" Hemlock bears S26W 49 lks; now a stump badly crushed by log.

RESTORED CORNER AND BEARING TREES

Set a 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T2S R7W S14 S13 S23 S24 1951 2311", 2 1/2 ft. in ground.

- 48" Fir stump bears N29E, 6.6 ft.; rescribed T2S R7W S13 2311 BT.
- 60" Fir stump bears S24E 33.7 ft.; rescribed T2S R7W S24 BT.
- 48" Fir stump bears S78W 22.1 ft.; scribed T2S R7W S23 BT.
- 24" Fir stub bears N79W 55.0 ft.; scribed T2S R7W S14 BT.

Placed an Oregon State Board of Forestry metal location poster on the 60" Fir stump BT and marked it; Sec 24 T2S R7W Sec Cor 51 lks N24W.

Dated December 31, 1951.

This corner was restored by Arnold G. Gibson
 Arnold G. Gibson Assistant Engineer
 under my direction.



Present and witnessed by Don D. Davis
 Don D. Davis Assistant Forest Engineer

Present and witnessed by Richard A. Morris
 Richard A. Morris Compassman