

BOUNDARY SURVEYS

SECTIONS 17 & 18, T2N, R6W, W.M.

NOTE 6: May 8, 1957, at the corner to sections 17, 18, 19 & 20, T2N, R6W, W.M. I find an OSBF galvanized iron pipe from which original BT's bear as follows:

A fir 36" diameter bears N 49° W 35.2 feet marked T2N S18 R6W (BT not chopped out).

A fir 30" diameter bears S 81° W 10.5 feet bearing the cruiser's mark "S". Original scribing not visible.

A hemlock 24" diameter bears E 44° E 27.6 feet bearing cruiser's mark "E". Original scribing not visible.

A rotted hemlock stump bears S 26° 30' E 8 feet. The log lying up the hill blazed and marked with cruiser's mark "A".

NOTE 7: May 8, 1957, at the $\frac{1}{4}$ corner between sections 17 & 20, T2N, R6W, W.M. I find an OSBF pipe marked $\frac{1}{4}$ S17 S20 1951 199 from which original BT's bear as follows:

A hemlock stump 32" diameter bears N 79° E 15.5 feet marked $\frac{1}{4}$ S BT.

A fir stump 26" diameter bears S 70° W 24.4 feet marked BT, the balance of the blaze being rotted away.

NOTE 8: May 14, 1957, at the $\frac{1}{4}$ corner between sections 19 & 20, T2N, R6W, W.M. I find lying on the ground a post 4" x 6" x ~~11~~ 6' long from which original BT's bear as follows:

A fir stump, badly rotted, 20" diameter bears N 51° E 13 feet marked S and BT; the balance of the scribing was chopped away when springboards were set.

A fir stump 48" diameter bears S 25° W 21 feet. No scribing is visible in the portion of the blaze chopped out. I do not chop out the balance of the blaze. I replace the post with a 1 $\frac{1}{2}$ " galvanized iron pipe 30" long set 20" in the ground.

NOTE 9: May 28, 1957 at the Closing Corner between sections 18 & 19, T2N, R6W, W.M. I find the original stone marked CC on the East face and the original BT's. Beside the stone I find an OSBF pipe; and a new BT stump is scribed 51 feet south.

NOTE 10: May 28, 1957 at the corner of sections 13 & 24, T2N, R7W, W.M. I find a Crown-Zellerbach pipe and an original BT.

NOTE 11: Midway between the Closing Corners for section 19, T2N, R6W, W.M., and on line between the corner to sections 13 & 24, T2N, R7W, W.M. and the east $\frac{1}{4}$ corner of said section 24, for the $\frac{1}{4}$ corner of section 19, T2N, R6W, W.M., I set a 1 $\frac{1}{2}$ " galvanized iron pipe 30" long 20" in the ground from which:

A stump 36" diameter bears N 59° E 61.2 feet marked $\frac{1}{4}$ S19 BT 322.

A stump 40" diameter bears S 53° E 19.1 feet marked $\frac{1}{4}$ S19 BT.