

County Surveyor's Record, Tillamook County Oregon

T 3 S. R. 8 W.

Rewitnessed corners

Mervin Whitmore, U. S. Forest Service

<p>18 17 18 17</p>	<p>Set iron pipe for cor. A 24" dead fir stub, N.62°W. 30 lks. mkd BT. (Old BT) A 12" dead fir, fallen, S.50°30'E. 19 lks. (Old BT) A 16" hemlock, N.77°W. 21½ ft. mkd ¼S18BT. (Old BT) A 12" hemlock, N.71°30'E. 15½ Ft. mkd ¼S17BT. (New BT) In the presence of Milt Easton Sept. 14, 1957.</p>
<p>17 16 20 21</p>	<p>Set a fir limb post 30" high for cor. A 50" dead fir snag, (not a 5" fir as per old records) N.10°W. 46 lks. (Old BT) with old scribe marks. A 24" alder, N. 47°E. 90 lks. with scribing. (Old BT) A 22" dead fir stub, S.29°30'E. 84 lks. (Old BT) A 22" fir, N.87°W. 35 ft. mkd. T3SR8WS17BT. (New BT) A 7" fir, N.24°E. 9 ft. mkd. T3SR8WS16BT. (New BT) A 5" fir, S.15°E. 17 ft. mkd. T3SR8WS21BT. (New BT) A 20" alder, S.43°30'W. 17½ ft. mkd. T3SR8WS20BT. (New BT) In the presence of L. E. Peterson June 5, 1958</p>
<p>6 5 7 8</p>	<p>The original stone with 5 notches on S. side. A 15" fir, S.57°E. 14½ ft. mkd. T3SR8WS8BT. (New BT) A 17" fir, N.76°30'E. 36.7 ft. mkd. T3SR8WS5BT. (New BT) A 14" fir, N.19°W. 11 ft. mkd. T3SR8WS6BT. (New BT) A 15" fir, S.83°W. 15 ft. mkd. T3SR8WS7BT. (New BT) A dead fir snag N.89°30'W. 74 lks. with old scribe marks. (Old BT) In the presence of Sam Seals and Daryl Watt. Aug., 11, 1958</p>
<p>7 8</p>	<p>Set post for cor. A 15" fir, N.77°E. 18 ft. mkd. ¼S8BT. (New BT) A 10" fir, S.78°W. 5 ft. mkd. ¼S7BT. (New BT) Both original BTs have scribing. In the presence of DeWayne Seufert. July 23, 1958</p>
<p>23 26</p>	<p>Set post for cor. A 30" fir, S.11°E. 48 ft. mkd. ¼S26BT. (New BT) A 12" fir, N.76°W. 30 ft. mkd. ¼S23BT. (New BT) In the presence of Renne Elisar and Perry Ackerman June 7, 1957</p>

(T. 3 S. R. 8 W.)