

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

Center South One Sixteenth corner for Section 14,
T1N, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S 1/16 C---C S14 1959 RS401", 48 inches in ground covered over with dirt, and from which a:

20" Apple tree bears S80 $\frac{1}{2}$ E 41.9 ft.; scribed CS 1/16 S14 BT RS401.
5" Alder bears S26 $\frac{1}{2}$ W 38.8 ft.; scribed in bark CS 1/16 S14 BT.

Oregon State Board of Forestry metal location poster on 20" Apple tree BT.
Set 4" x 4" x 60" white painted Cedar post 1.0' S.E. of pipe.
Corner point falls in E. edge of pastured bottom land.

Center One Quarter corner for Section 23, T1N,
R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E


Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY C 1/4 S23 1959 RS401", 31 inches in ground, in mound of stone, and from which a:

20" Spruce bears N21E 34.1 ft.; scribed C 1/4 S23 BT RS401.
17" Spruce bears S3E 35.4 ft.; scribed C 1/4 S23 BT.
48" Creek bears N2E 82.0 ft.; course N45W.
48" Creek bears East 22.0 ft. course N30E.

Oregon State Board of Forestry metal location poster on 20" Spruce BT.
Set 4" x 4" x 60" white painted Cedar post 1.0' S.W. of pipe.

Dated December 31, 1959

Established by



Richard A. Morris



Present and witnessed by R. Cop
E. Nylund