

CHAINS

REESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

One Quarter corner common to Sections 24 and 25, T1N,
R10W, W.M., Tillamook County, Oregon.

REESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY 1/4 S24 S25 1959 RS401", 33 inches in ground, in mound
of stone, and from which a:

- 30" Fir bears N27 $\frac{1}{2}$ E 19.1 ft.; scribed 1/4 S24 BT RS401.
- 23" Fir bears S86E 15.0 ft.; scribed 1/4 S25 BT.

Oregon State Board of Forestry metal location poster on 23" Fir BT.
Set 4" x 4" x 60" white painted Cedar post 1.0' N.E. of pipe.

* * * * *

One Quarter corner common to Sections 25 and 30,
T1N, R9 & 10W, W.M., Tillamook County, Oregon.

REESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY 1/4 S25 S30 1959 RS401", 30 inches in ground, in mound
of stone, and from which a:

- 17" Hemlock bears N62 $\frac{1}{2}$ E 47.7 ft.; scribed 1/4 S30 BT RS401.
- 10" Hemlock bears N21 $\frac{1}{2}$ W 28.0 ft.; scribed 1/4 S25 BT.
- 12" Creek and 4' water fall bears North 41.0 ft.; course S25E.
- 12" Creek bears South 28.0 ft.; course S30W.

Oregon State Board of Forestry metal location poster on 17" Hemlock BT.
Set 4" x 4" x 60" white painted Cedar post 1.0' S.W. of pipe.

Dated December 31, 1959

Reestablished by



Richard A. Morris



Present and witnessed by H. Russell
R. Cop
E. Nylund
D. Jones