

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY  
 (See official plat)  
 Southwest One-sixteenth corner for Section 10, T1N,  
 R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SW 1/16 S10 1961 RS401", 24 inches in ground, in small mound of rock, and from which a:

- 27" Hemlock bears S33E 0.8 ft.; scribed SW 1/16 S10 BT RS401.
- 24" Hemlock bears N15½W 49.6 ft.; scribed SW 1/16 S10 BT.

Set 4" x 4" x 52" white painted Cedar post 2.6 ft. S.E. of corner pipe. Oregon State Board of Forestry metal location poster on 27" Hemlock BT.

\* \* \* \* \*

North One-sixteenth corner common to Sections 13 and 18, T1N, R9 & 10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N 1/16 S18 S13 1961 RS401", 32 inches in ground, and from which a:

- 19" Hemlock bears N47½W 32.0 ft.; scribed N 1/16 S13 BT RS401.
- 22" Hemlock bears N39E 18.8 ft.; scribed N 1/16 S18 BT.


Set 4" x 4" x 52" white painted Cedar post 1.0 ft. S.E. of corner pipe. Oregon State Board of Forestry metal location poster on 22" Hemlock BT.

Dated February 27, 1961

Established by



*Richard A. Morris*



Present and witnessed by H. Russell  
 R. Cop  
 E. Nylund