

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)

South One-sixteenth corner for Section 36, T1S, R9W,
W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY S 1/16 S36 1961 RS526", 35 inches in ground, and from
which a:

34" Spruce bears N68 1/2 W 271.5 ft.; scribed S 1/16 S36 BT RS526.

Set 4 x 4 x 72" white painted Cedar post 0.7 ft. NW of corner pipe.
Oregon State Board of Forestry metal location poster on post 0.7 ft.
NW of pipe.

* * * * *

Witness one quarter corner for Section 31, T1S, R8W,
W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY WC 50' N 1/4 S31 1961 RS526", 33 inches in ground,
on South bank of Trask River, 50.0 ft. S0°26'29" E of true 1/4 corner,
and from which a:

28" Spruce bears S54E 77.0 ft.; scribed WC 1/4 S31 BT.
9" Alder bears S3E 21.4 ft.; scribed RS526.

Set 4 x 4 x 72" white painted Cedar post 1 ft. NW of corner pipe.
Oregon State Board of Forestry metal location poster on 9" Alder S46E 10.1 ft.

Dated May 23, 1961

Established by

Present and witnessed by E. Driver
J. Hollingsworth
E. Poitras

* * * * *

(East Side) One Quarter corner for Section 36, T1S, R9W, W.M.,
Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY 1/4 S36 1961 RS526", 33 inches in ground, and from
which a:

20" Hemlock bears S52W 25.1 ft.; scribed 1/4 S36 BT.
16" Hemlock bears S56E 15.1 ft.; scribed RS526.

Set 4 x 4 x 72" white painted Cedar post 1.5 ft. SW of corner pipe.
Oregon State Board of Forestry metal location poster on 20" Hemlock BT.

Dated May 23, 1961

Established by

Present and witnessed by C. Skog
E. Poitras

REGISTERED
OREGON
LAND SURVEYOR

David W. Steenson
NOV. 11, 1960
David W. Steenson
526

REGISTERED
OREGON
LAND SURVEYOR

David W. Steenson
NOV. 11, 1960
David W. Steenson
526