

Dependent Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS

- 32.40 Gravelled road, 40 lks. wide; bears N. and S.; also power line, bears along road.
- 36.00 Leave creek, course N. 55° W.; asc. 5 ft. over NE. slope.
- 37.00 Top of left bank of Nestucca River, bears NE. and S. 20° W.; desc. 10 ft. over gradual W. slope of rocky river bottom.
- 39.58 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner. The corner point is located at the left edge of water in the Nestucca River, 70 lks. wide, course S. 20° W., where it is impracticable to establish a permanent monument.
- 40.30 Right edge of river; asc. 35 ft. over river bank.
- 41.80 Top of right bank bears NE. and S.; asc. 10 ft. over E. slope.
- 42.58 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- WC
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{6}{7}$ →
 T 4 S R 7 W
 1965
- from which
- A fir, 38 ins. diam., bears N. 19° E., $168\frac{1}{2}$ lks. dist., mkd. X at breast height and BT at the base.
- An alder, 20 ins. diam., bears S. 61° W., $45\frac{1}{2}$ lks. dist., bark scribed X at breast height and BT at the base.
- Ascend 55 ft. over E. slope.
- 44.60 Ravine, drains S. 55° E.; asc. 190 ft. over NE. slope.
- 50.40 Head of same ravine, drains N. 70° E.; asc. 220 ft. over steep E. slope, and rock bluff.
- 53.40 Top of rock bluff, 100 ft. high, bears N. and S.; asc. 270 ft. over steep NE. slope.
- 59.00 Spur, slopes SE.; asc. 5 ft. along broken S. slope.
- 64.50 Top of ascent, slopes S.; desc. 280 ft. over SW. slope.
- 79.60 The cor. of secs. 1, 6, 7, and 12.

Land, mountainous.

Soil, sandy loam and clay.

Timber, fir, alder, maple, cascara, and wild cherry; undergrowth, vine maple, salal, huckleberry, willow, devil's club, fern and nettle.

From the cor. of secs. 5, 6, 7, and 8.