

Dependent Resurvey of Base Line, Portion of S. Bdy. of T. 1 N., R. 9 W.

	Chains 19.58	Point for the E 1/16 sec. cor. of Section 34 only. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
		<u>E 1/16 S 34</u> 1959
		from which
		A hemlock, 20 ins. diam., bears N. 34½° E., 114 lks. dist., mkd. E 1/16 S 34 BT.
		A hemlock, 25 ins. diam., bears N. 48° W., 115 lks. dist., mkd. E 1/16 S 34 BT.
		The corner falls at the corner of timber, edges bear N. and E.
		Descend 60 ft. over SW. slope, through open logged area.
26.14		Abandoned logging road, 20 lks. wide, bears NW. and SE.
24.40		Leave logged area and benchland, edge bears NW. and SE.; enter heavy timber and light undergrowth.
25.00		Bottom of descent, drains S.; ascend 66 ft. over SE. slope.
27.00		Spur, slopes S.; descend 133 ft. over SW. slope.
30.50		Spring branch, 1 lk. wide, course S.; ascend 60 ft. over SE. slope.
32.00		Spur, slopes S.; descend 175 ft. over SW. slope.
36.30		Top of slide area and rocky outcropping, bears NW. and SE.
37.055		Point for the ½ sec. cor. of Section 3 only, on the W. bdy. of T. 1 S., R. 9 W., hereinafter described.
		Descend 53 ft. over steep SW. slope of slide area and rock outcropping.
39.16		Point for the ½ sec. cor. of Section 34 only, at proportionate distance; there is no remaining evidence of the original corner.
		Cement a brass tablet, 3½ ins. diam., 3½ in. stem, in a drill hole in exposed bedrock, with top mkd.
		<u>T 1 N R 9 W</u> <u>½ S 34</u> 1959
		from which
		A fir, 30 ins. diam., bears N. 22° E., 93 lks. dist., mkd. ½ S 34 BT.
		A fir, 41 ins. diam., bears N. 35° W., 141½ lks. dist., mkd. ½ S 34 BT.
		The corner falls at the W. edge of slide area and rock outcropping bearing NW. and SE.
		Descend 310 ft. over steep, rocky SW. slope, changing to W. slope.
45.50		Branch, 3 lks. wide, course S. 10° W.; ascend 360 ft. over steep rocky SE. slope.

105