## Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains 50.81

Point for the W 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 22 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 12 S 13

from which

- A hemlock, 21 ins. diam., bears N. 562 W., 582 lks. dist., mkd. W 1/16 812 BT.
- A spruce, 30 ins. dism., bears S.  $57\frac{1}{2}$  E., 30 lks. dist., mkd. W 1/16 S13 BT.

The corner fells in a trail bearing NE. and SW.

Ascend 87 ft. over SE. slope.

- 56.80 Branch, 3 lks. wide, course S.; asc. 226 ft. over E. slope, changing to S. slope, through heavy old growth timber and light undergrowth.
- 67.30 Spur, slopes S. 20° W.; desc. 50 ft. over SW. slope.
- 68.64 The cor. of secs. 12 and 13, on the E. bdy. of sec. 14.

Land, mountainous except for narrow river bottom.

Soil, rocky clay with loam in the river bottom.

Timber, spruce, hemlock, fir, cedar, alder, maple, and cascara; undergrowth, salmonberry, vine maple, salal, and reproduction.

From the cor. of secs. 11 and 14 on the W. bdy. of sec. 12.

N. 9° 24' W., bet. secs. 11 and 12.

Ascend 100 ft. over steep rocky SW. slope, through heavy timber and light undergrowth.

- 4.20 Wet mavine, drains S. 20° W.; asc. 360 ft. over steep, rocky SE. slope, changing to S. slope.
- 10.05 Foot of cliff, 30 ft. high, edge bears E. and W.; asc. 257 ft. over steep, rocky S. slope, changing to SE. slope.
- 15.50 Ridge, bears NE. and SW.; desc. 21 ft. over NW. slope.
- 17.14 Point for the \$ 1/16 sec. cor. of secs. 11 and 12.

Set an iron post, 28 ins. long, 22 ins. diam., 24 ins. in the ground, with brass cap mkd.

from which

- A fir, 16 ins. diam., bears N. 15° E., 9 lks. dist., mkd. S 1/16 S12 BT.
- A fir, 23 ins. diam., bears S. 46° W., Il lks. dist., mkd. S 1/16 511 BE.

U. S. GOVENNMENT PRINTING OFFICE

Descend 200 ft. over NW. slope.

128