

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains

To complete the survey of sec. 12, I return to the cor. of secs. 6 and 7 only, on the W. bdy. of T. 1 S., R. 9 W., and run

N. $1^{\circ} 33'$ E., along the E. bdy. of sec. 12.

9.45 Point for the $\frac{1}{4}$ sec. cor. of sec. 12 only, at proportionate distance in latitude, on the E. bdy. of sec. 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 1 S |
 $\frac{1}{4}$ S 12 |
 R 9 W |
 1959

from which

A hemlock, 15 ins. diam., bears S. 54° W., 91 lks. dist.,
mkd. $\frac{1}{4}$ S12 BT.

A hemlock, 15 ins. diam., bears N. 77° W., $63\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S12 BT.

From the cor. of secs. 1, 2, 11, and 12.

N. $0^{\circ} 28'$ W., bet. secs. 1 and 2.

Ascend 162 ft. over SE. slope, changing to E. slope, through heavy timber and dense undergrowth.

9.55 Spur, slopes E.; desc. 92 ft. over NE. slope.

12.75 Wet ravine, drains N. 60° E.; asc. 243 ft. over SE. slope.

19.70 Leave live timber, edge bears NE. and SW.; enter dead timber and dense reproduction.

28.83 Main ridge, dividing Kilchis River and Wilson River drainage, bears N. 20° E. and S. 30° W.; desc. 97 ft. over steep, rocky NW. slope, changing to W. slope.

35.63 Bottom of descent, drains W.; asc. 180 ft. over SW. slope.

42.66 Same ridge, bears N. 20° W. and S. 25° E.; desc. 55 ft. over NE. slope.

47.90 Bottom of descent, drains E.; asc. 25 ft. over SE. slope.

48.89 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 1 S R 9 W
 ↑
 S 2 S 1
 1960

from which

A fir, 6 ins. diam., bears S. $32\frac{1}{2}^{\circ}$ E., $44\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S1 BT.