

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 1 S R 9 W ½ S 14 1958</p>
	from which
	A fir, 50 ins. diam., bears N. 36° E., 29½ lks. dist., mkd. ½ S14 BT.
	A fir, 30 ins. diam., bears S. 63½° E., 7½ lks. dist., mkd. ½ S14 BT.
	Ascend 126 ft. over S. slope.
39.04	Point for the ¼ sec. cor. of sec. 15 only, on the E. bdy. of sec. 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 1 S R 9 W ¼ S 15 1958</p>
	from which
	A spruce, 20 ins. diam., bears S. 58½° W., 64½ lks. dist., mkd. ¼ S15 BT.
	A hemlock, 30 ins. diam., bears N. 11½° W., 44 lks. dist., mkd. ¼ S15 BT.
	Ascend 588 ft. over steep rocky S. slope.
55.40	Ridge, bears N. 70° W. and E.; desc. 18 ft. over NW. slope, through heavy timber and light undergrowth.
58.58	Point for the N 1/16 sec. cor. of sec. 15 only, on the E. bdy. of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">N 1/16 S 15 1958</p>
	from which
	A fir, 37 ins. diam., bears S. 58½° W., 85 lks. dist., mkd. N 1/16 S15 BT.
	A fir, 32 ins. diam., bears N. 86½° W., 93 lks. dist., mkd. N 1/16 S15 BT.
	The corner falls at S. side of a spruce, 40 ins. diam.
	Descend 210 ft. over N. slope, changing to W. slope, along E. side of a wet ravine, coursing N.
64.75	Branch, 2 lks. wide, course N. 70° E.; asc. 30 ft. over SE. slope.