

Resurvey of Portion of North Boundary of

T. 3 S., R. 10 W.

Chains.					
	<p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 32 and 33 only, with brass cap mkd.</p> <p style="text-align: center;"> <table border="1"> <tr> <td>T2S</td> <td>R10W</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> </table> </p> <p style="text-align: center;">T3S R10W S5 1933</p> <p>from which</p> <p>A hemlock, 36 ins. diam., bears N. 36° E., (not N. 37° E.) 42 lks. dist., marks overgrown. (Old B. T.)</p> <p>A hemlock stump, 40 ins. diam., bears N. 11 W., (not N. 10° W.) 34 lks. dist., mkd. S 32 B T. (Old B. T.)</p> <p>A hemlock, 6 ins. diam., bears N. 40° W., 59 lks. dist., mkd. T 2 S R 10 W S 32 B T. (New B. T.)</p> <p>Land, mountainous, rolling. Soil, sandy loam, 3rd rate. Timber, hemlock, spruce, cedar, and alder. Undergrowth, vinemaple, salal, alder, fern, Devil's claw and wild blackberry.</p>	T2S	R10W	S32	S33
T2S	R10W				
S32	S33				
	<p>S. 89° 42' W., on true line on S. bdy. of sec. 32.</p> <p>Asc. 161 ft. over E. slope, through heavy timber and dense undergrowth.</p> <p>7.70 Spur, slopes NE., over rolling land.</p> <p>13.20 Asc. 357 ft. over steep E. slope.</p> <p>24.50 Point for 1/4 sec. cor. of sec. 5 only, determined as hereinafter set forth.</p> <p>32.00 Top of ascent, bears SW. and NE., desc. 51 ft. over W. slope.</p> <p>38.00 Thence over level land.</p> <p>40.02 Point for 1/4 sec. cor. of sec. 32 only, as determined by reference to original tree cor., which is a hemlock, 38 ins. diam., dead and fallen, mkd. 1/4 S.</p> <p>At point for 1/4 sec. cor., in center of stump hole of tree cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in ground to bedrock, and in a mound of stone to the top for 1/4 sec. cor. of sec. 32 only, with brass cap mkd.</p> <p style="text-align: center;">1/4 S32</p> <p style="text-align: center;">1933</p> <p>from which</p> <p>A hemlock, 30 ins. diam., bears N. 28 1/2° E., 26 lks. dist., mkd. 1/4 S 32 B T. (New B. T.)</p> <p>A hemlock, 10 ins. diam., bears N. 47° W., 37 lks. dist., mkd. 1/4 S 32 B T. (New B. T.)</p>				