

County Surveyor's Record, Tillamook County, Oregon

TOWNSHIP 6 SOUTH, RANGE 10 WEST

PROPERTY CORNER 429.0 FT. SOUTH OF C.N. 1/16 CORNER (NOT SET) SEC. 3, T6S, R10W

SET 1 1/4" STAINLESS STEEL PIPE.

5

SCRIBED THE FOLLOWING B.T.'S.:

32" SPRUCE BEARS N 64°E 25.4 FT. S. NAIL, L. WASHER, Y. TAG  
18" HEMLOCK BEARS S 48°W 45.0 FT. S. NAIL, L. WASHER, Y. TAG

CORNER SETS IN BOTTOM OF CREEK JUNCTION. BEARING OF CREEK DOWNSTREAM S 24°W;  
UPSTREAM N 10°E (100') AND N55°E (30' THEN EAST).

MAY 10, 1967 SET BY: R. STEWART  
WITNESSES: R. ENGLAND, D. WILLIAMS

S-W 1/16 CORNER, SECTION 3, T6S, R10W

SET 1 1/4" STAINLESS STEEL PIPE.

5

SCRIBED THE FOLLOWING B.T.'S.:

40" HEMLOCK BEARS S 83°W 48.20 FT. S. NAIL, L. WASHER, Y. TAG  
58" SPRUCE BEARS S 02°E 29.10 FT. S. NAIL, L. WASHER, Y. TAG

CORNER SETS ON OLD CUTTING LINE (15 YEARS). BEARING NE AND SW.

MAY 11, 1967 SET BY: R. STEWART  
WITNESSES: R. ENGLAND, L. WHITEMORE

1/4 CORNER, SECTIONS 4/3, T6S, R10W

SET 1 1/4" STAINLESS STEEL PIPE.

4

SCRIBED THE FOLLOWING B.T.'S.:

28" SPRUCE BEARS S 14°W (?) FT. S. NAIL, L. WASHER, Y. TAG  
33" FIR BEARS N 34°E 45.8 FT. S. NAIL, L. WASHER, Y. TAG

ASPECT S.E. 60%.  
CORNER IS 40 FT. EAST OF DIRT ROAD BEARING N 50°E.

MAY 12, 1967 SET BY: R. STEWART  
WITNESSES: R. ENGLAND, L. WHITEMORE

W 1/16 CORNER, SECTIONS 3, T6S, R10W  
10

SET 1 1/4" STAINLESS STEEL PIPE.

5

SCRIBED THE FOLLOWING B.T.'S.:

5" HEMLOCK BEARS N 21°E 11.2 FT. S. NAIL, L. WASHER, Y. TAG  
49" SPRUCE BEARS S 49°E 46.2 FT. S. NAIL, L. WASHER, Y. TAG

ASPECT S-W 20%  
CORNER SETS IN 15 YR. OLD REPROD. 40' WEST OF OLD CUTTING LINE AND 3 CHAINS  
EAST OF ROAD.

MAY 12, 1967 SET BY: R. STEWART  
WITNESSES: R. ENGLAND, L. WHITEMORE

