


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

(Reference FSH 5681.65)

History of original corner establishment:

Corner originally established by Henry Meldrum in 1878. U.S. Forest Service Records at Hebo indicates the Tillamook County surveyor in 1895 set a 4 x 8 x 22 stone mkd + on top and C.S. on North Side.




Description of corner evidence found:

Found a 22 x 8 x 4 stone mkd + on top side and C.S. on north side from which

The original NW Maple BT BRG N83W 57.4 ft.
M. Whitmore's SW & Alder BT--1963
NW

Description of monument and accessories established to perpetuate the original location of this corner

Set 2" x 30" iron pipe with brass cap mkd



Set original rock on north side of pipe mkd
2 new BT's

An 8" alder N34E 35.5', scribed T4s R9W s 33 BT

A 26" alder s74E 18.5', scribed T5s R9W s 4 BT

Set tags

Set steel post approximately 5 feet facing south and west

REGISTERED
OREGON
LAND SURVEYOR

Tom O. McCullough

JULY 10, 1964
TOM O. McCULLOUGH
650

Office of County of
State of , I hereby certify that the within instrument was filed in this office
for record on the day of; 19....., at o'clockm., (signed)
..... by
(COUNTY OFFICIAL) (DEPUTY)