


History of original corner establishment:

Corner set by William Anderson, Tillamook County Surveyor, in February, 1951.



Description of corner evidence found:

1" pipe 3" above ground from which

A 16" lodge pole pine brs N9W 34.9 ft; scibing pitched over but just visible; F.S. tag good

An 11" fir brs S11E 27.7 ft; face healed over; tag good

A 14" lodge pole pine snag brs S78W 22.9 ft; scribed S1/16 (error) BT New tag

Description of monument and accessories established to perpetuate the original location of this corner

Set a 30" iron pipe with brass cap mkd

T 3 S R 10 W

E 1/16	<u>7</u>
	18
	1969
	650

Placed original pipe along side brass cap.

Placed a 6' steel post west of corner with F.S. boundary sign facing north

Placed a 6' steel post north of corner with F.S. boundary sign facing west.

Painted red band around each BT

No new BT's.

REGISTERED  
OREGON  
LAND SURVEYOR

*Tom O. McCullough*  
JULY 10, 1964  
TOM O. McCULLOUGH  
650

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the ..... day of.....; 19....., at..... o'clock .....m., (signed)  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)