


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1880. L. Whitmore found the remains of Caudle's stone at near the record distance from the NW corner of section 16. (see attached USFS card).



Original monument: stone 16 x 12 x 8 for $\frac{1}{4}$ corner & built stone mound.

Description of corner evidence found:

Found a crumbly stone 8x8x6 with smaller pieces underneath. A galvanized steel post and 2"x2" Vine Maple post beside stone. Approximately 14 feet N12E was a 26" fir with X and location poster giving location of stone as approximately $\frac{1}{4}$ corner.

No bearing trees found.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 2"x30" iron pipe with brass cap mkd

T5S R9W
 $\frac{1}{4}$ $\frac{9}{16}$
 1969
 650

from which

Fir brs. S70E 49.4 ft. (slope)
scribed $\frac{1}{4}$ S16 BT 650

26" fir brs. N13W 13.9 ft.
scribed $\frac{1}{4}$ S9 BT

Set steel fence post 3 feet north of cap with F.S. boundary and attention signs facing west; placed BT tags and painted red band on BT's.

Set steel post and wood post beside cap.

Office of County Surveyor County of Tillamook
 State of OR, I hereby certify that the within instrument was filed in this office
 for record on the 2nd day of February, 1970, at 10 o'clock am, (signed)
[Signature] by [Signature]
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
 OREGON
 LAND SURVEYOR

February 2, 1970

[Signature]
 JULY 10, 1964
 TOM O. McCULLOUGH
 650

BOOK 3

Form R6-7100-57 (9/66) BK-85