


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in May of 1882 by William  
~~P. Wright~~ J.W. Maldrum.



Description of corner evidence found:

Found 1" pipe set by L. Whitmore in May of 1962 from which

50" snag brs. N29E 105.5 ft - with tag - scribing -  
lower half of B visible (N33E) (orig)

50" fir snag brs. S50W 35.0 ft - no marks (orig)

40" fir snag brs. S12E 41.0 ft - no marks (orig)

14" fir brs. S50W 46.0 ft - scribed - with tag

24" fir brs. N21½W 28.2 ft - scribed - with tag

10" cedar brs. S27E 34.4 ft - scribed - with tag


36" fir brs. N59E 17.0 ft - scribed - with tag

established by  
L. Whitmore  
5/11/62

Description of monument and accessories established to perpetuate the  
original location of this corner

Set 2"x30" iron pipe with brass cap mkd

T3S R10W



T4S  
1970  
650

Placed 1" pipe alongside corner

Set a fence post with signs + 5 ft west facing south

Office of Tillamook County of Surveyor  
State of OR, I hereby certify that the within instrument was filed in this office  
for record on the 13 day of May, 1970, at ..... o'clock .....m., (signed)  
[Signature] by .....  
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED  
OREGON  
LAND SURVEYOR

[Signature]  
JULY 10, 1964  
TOM O. McCULLOUGH  
650

BOOK 3

363