


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in May of 1882 by ~~William P. Wright~~. J.W. Maldrum.




Description of corner evidence found:

Found 1½" galvanized pipe (old)  
Found old post with face on one side - wired to pipe from which

- 50" fir snag brs. N40W 64.5 ft. (orig)
  - 80" fir snag brs. S52W - no scribing (orig)
  - 18" alder brs. N49W 29.5 ft  
bark scribed - with tag
  - 20" alder brs. S66W 31.0 ft  
bark scribed - with tag
  - 16" fir brs. S48E 44.2 ft  
scribed - with tag
  - 24" fir brs. N29E 45.0 ft  
scribed - with tag
- established by M. Whitmore  
9/31/58

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap mkd



Set 1½" pipe alongside corner

Set fence post ± 5 ft south facing west (with sign)

Office of T. Williams County of SURSEY  
 State of OREGON, I hereby certify that the within instrument was filed in this office  
 for record on the 13<sup>th</sup> day of May, 1970, at        o'clock        m., (signed)  
[Signature] by        (DEPUTY)  
 (COUNTY OFFICIAL)

REGISTERED  
 OREGON  
 LAND SURVEYOR

[Signature]

JULY 10, 1964  
 TOM O. McCULLOUGH  
 650

BOOK 3

367