


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner set in 1900 by Tillamook County Surveyor. The corner was set by proportionate measure between the existing original Southwest corner and South 1/4 corner of Section 23, T3S, R9W, W.M. A Fir stake was set for the corner with 2 bearing trees as follows:

- A 40" Fir bears S 21° E 77 links
- A 60" Fir bears S 82° E 59 links



Description of corner evidence found:


The corner was re-witnessed in 1970 by Leonard Whitmore, Tillamook County Deputy Surveyor. He found both 1900 bearing trees, now snags, with scribing visible on one. He set a 3" X 3" vine maple post at the intersection of the recorded distances. He marked 2 B.T.'s as follows:

- A 17" Fir, bears N 28° W 18.8 feet to a nail head at scribed "B" on face, marked W 1/16, S26, B.T., C.S.
- An 18" Alder, bears S 5° W 31.5 feet to a nail head at scribed "B" on face marked W 1/16, S26, B.T., C.S.

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the 3" X 3" stake I placed a galvanized iron pipe 30" long and 2" in diameter, with circular flange at bottom and capped with a brass disk welded to the top of the pipe. The monument projects 4" above the ground.

I stamped the disk →



From the pipe monument the 1970 bearing trees are as follows:

- An 18" Douglas Fir bears N 28° W 18.8 feet to the scribed face.
- A 22" Alder bears S 5° W 31.5 feet to the scribed face.

Office of County Surveyor County of Tillamook
 State of Oregon I hereby certify that the within instrument was filed in this office
 for record on the 29 day of July, 1970, at o'clock m., (signed)
 [Signature] by [Signature] County Surveyor
 (COUNTY OFFICIAL) (DEPUTY)

