


CERTIFIED RECORD OF LAND CORNER MONUMENT

History of original corner establishment:

Corner originally set by Morris Wygant in 1908. He set post and scribed a hemlock and fir BT
L. Whitmore found corner in 1970 and scribed 2 new BTs.



Description of corner evidence found:

Found a hemlock stake (L. Whitmore, 1970)
Found a rotted square stake (not orig) from which

A 7" fir brs. N15E 9.8 ft (Whitmore, 1970)
X at DBH scribed BT 12" above ground

An 8" hemlock brs. S68W 14.8 ft (Whitmore, 1970)
marked X at DBH and BT 12" above ground

A 30" hemlock stump brs. N83¹/₂E 19.8 ft
face rotted away but over growth visible

Description of monument and accessories established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap marked

T6S R9W

$\frac{1}{4}$ 8 | 9

1970
920

Set stakes beside corner

Set steel fence post 2 ft east of corner with F.S. boundary signs and attention signs attached facing south.

Painted BTs and attached BT tags.

Bark scribed Whitmores 2 BTs as follows:

7" fir scribed $\frac{1}{4}$ S9 BT

8" hemlock scribed $\frac{1}{4}$ S8 BT

Office of COUNTY SURVEYOR County of TILLAMOOK
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 9th day of SEPTEMBER, 1970, at o'clock m., (signed)
[Signature] CO. SURVEYOR by (DEPUTY)

REGISTERED
OREGON
LAND SURVEYOR

[Signature]
JULY 17, 1970
RICHARD L. BRYANT
920

BOOK 3

373