

N 1/16 CORNER BETWEEN SECTIONS 1 AND 2 ESTABLISHED

Set by proportionate measurement, a 1"X36" pipe with brass cap marked N 1/16 1,2 ORLS 650 from which

A 33" fir bears N70 $\frac{1}{2}$ E 19.5 feet on which  
I scribed N 1/16 S 1 BT 650

A 25" fir bears N76 $\frac{1}{2}$ W 48.6 feet on which  
I scribed N 1/16 S 2 BT

E 1/4 CORNER SECTION 2 REESTABLISHED

After an extensive search for corner, I set, by proportionate measurement, a 1"X36" pipe with brass cap marked 1/4 ORLS 650 from which

A 16" fir bears N79E 11.0 feet on which  
I scribed W 1/4 S 1 BT

A 19" fir bears S64W 14.5 feet on which  
I scribed E 1/4 S 2 BT

SE CORNER SECTION 2 REMONUMENTED

Set 1"X36" pipe with brass cap marked 1, 2, 11, 12 ORLS 650 beside original stone marked with one notch on south edge and one groove on east face from which

A 12" fir bears N7E 10.5 feet on which  
I scribed T4S R7W S 1 BT

A 18" fir bears S40E 33.0 feet on which  
I scribed T4S R7W S 12 BT

A 14" fir bears S68W 32.0 feet on which  
I scribed T4S R7W S 11 BT

A 11" fir bears N57W 19.0 feet on which  
I scribed T4S R7W S 2 BT

Found what appeared to be an original blaze on a snag about 25 feet due south of stone.

