

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 7 W.

Chains

T 4 S R 7 W
S 10 | S 11
S 15 | S 14
1961

from which

A fir, 20 ins. diam., bears N. 39½° E., 130 lks. dist.,
mkd. T4S R7W S11 BT.

A fir, 10 ins. diam., bears S. 20° E., 119 lks. dist.,
mkd. T4S R7W S14 BT.

A fir, 16 ins. diam., bears S. 82° W., 115 lks. dist.,
mkd. T4S R7W S15 BT.

A fir, 25 ins. diam., bears N. 71° W., 147 lks. dist.,
mkd. T4S R7W S10 BT.

Deposit the sandstone alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, alder, dogwood, and maple; undergrowth, vine maple, salal, huckleberry, salmonberry, fern, and reproduction.

From the corner of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with the original sandstone, now broken and weathered, 13 x 8 x 6 ins., with 1 notch visible on a fragment of broken stone, loosely set, alongside an iron pipe, 3/4 in. diam., protruding 3 ins. above ground, firmly set, in corner of fallen fence, extending S. and W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 7 W
S 33 | S 34
S 4 | S 3
T 5 S
1961

from which

A fir, 16 ins. diam., bears N. 79° E., 33½ lks. dist.,
mkd. T4S R7W S34 BT.

A fir, 12 ins. diam., bears S. 43° E., 38 lks. dist.,
mkd. T5S R7W S3 BT.

A fir, 15 ins. diam., bears S. 55° W., 15½ lks. dist.,
mkd. T5S R7W S4 BT.

A fir, 14 ins. diam., bears N. 35½° W., 45½ lks. dist.,
mkd. T4S R7W S33 BT.

Deposit the sandstone and iron pipe alongside the iron post.

N. 0° 52' W., bet. secs. 33 and 34.

Ascend 94 ft. over SW. slope, through heavy timber and light undergrowth.

3.20

Ridge and divide between Canada Creek and Gilbert Creek, bears E. and W.; desc. 132 ft. over N. slope, changing to broken NE. slope.

68
11