

Dependent Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS

from which

A fir, 28 ins. diam., bears N. 38° E., 30 lks.
dist., mkd. S1/16 S16 BT.

A fir, 17 ins. diam., bears N. 62° W., 20 lks.
dist., mkd. S1/16 S17 BT.

Ascend 65 ft. along W. slope.

29.00 Spur, slopes W.; desc. 155 ft. along W. slope, changing
to NW. slope.

35.60 Creek, 3 lks. wide, course S. 80° W.; asc. 65 ft. over
SW. slope.

36.50 Low spur, slopes S. 50° W.; desc. 15 ft. over NW.
slope.

37.20 Creek, 2 lks. wide, course S. 55° W.; asc. 90 ft. over
S. slope.

39.24 The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented with the
original basalt stone, 12 x 10 x 8 ins., firmly set 8
ins. in the ground, mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

$\frac{1}{4}$
S 17 | S 16

T 4 S R 7 W
1965

from which

A fir, 35 ins. diam., bears N. 61° E., 38 lks.
dist., mkd. $\frac{1}{4}$ S16 BT.

An alder, 22 ins. diam., bears N. 41 $\frac{1}{2}$ ° W., 37 lks.
dist., bark scribed $\frac{1}{4}$ S17 BT.

Deposit the original stone alongside the iron post.

N. 0° 03' W., beginning new measurement.

Ascend 120 ft. over S. slope.

4.50 Spur, slopes SW.; asc. 15 ft. along W. slope.

10.00 Head of ravine, drains SW.; asc. 155 ft. over S. slope,
changing to SW. slope.

22.70 Dirt road, 10 lks. wide, bears N. 10° W., curving to N.,
and S. 30° E., curving to E.

23.60 Spur, slopes W.; desc. 20 ft. over NW. slope.

23.90 Same road, bears N. 30° E., curving to N., and S. 30°
W. curving to S.

25.70 Bottom of descent, slopes W.; asc. 135 ft. over broken
SW. slope.

27.40 Same road, bears N. 35° W. and S. 30° E., curving to S.