

Dependent Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS

40.12

The cor. of secs. 8, 9, 16, and 17, monumented with the original basalt stone, 30 x 12 x 12 ins., firmly set 25 ins. in rock mound at foot of talus slope, mkd. with 2 notches on N., and 4 notches on E. edge.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. into loose talus rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 4 S R 7 W
S 8 | S 9
S 17 | S 16
1965

from which

A fir, 24 ins. diam., bears N. 12° E., 162 lks. dist., mkd. T4S R7W S9 BT.

A fir, 16 ins. diam., bears S. 50° E., 62 lks. dist., mkd. T4S R7W S16 BT.

A fir, 10 ins. diam., bears S. 43° W., 26 lks. dist., mkd. T4S R7W S17 BT.

A fir, 16 ins. diam., bears N. 78° W., $37\frac{1}{2}$ lks. dist., mkd. T4S R7W S8 BT.

Deposit the original stone alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, alder, cascara, wild cherry and maple; undergrowth, vine maple, fern, salal, willow, devil's club, Oregon grape and salmonberry.

From the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with the original broken sandstone, 12 x 8 x 7 ins., loosely set 3 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 19 | S 20
T 4 S R 7 W
1965

from which

A fir, 13 ins. diam., bears N. 76° E., 31 lks. dist., mkd. $\frac{1}{4}$ S20 BT.

A fir, 9 ins. diam., bears N. 79° W., 33 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

Deposit the original stone alongside the iron post.

N. 2° 56' E., bet. secs. 19 and 20.

Ascend 100 ft. over S. slope, through medium timber and dense undergrowth.

BOOK 3