

Dependent Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS	
28.40	Same road, bears NE. and SW.
31.00	Spur, slopes NW.; desc. 220 ft. over N. slope.
39.74	The cor. of secs: 5, 6, 31, and 32; on the N. bdy. of the Tp. Land, mountainous. Soil, rocky clay. Timber, alder, fir, cascara, wild cherry and spruce; undergrowth, vine maple, salal, fern, devil's club and nettle.
Subdivision of Section 17, T. 4 S, R. 7 W., Willamette Meridian, Oregon	
	From the $\frac{1}{4}$ sec. cor. of secs. 17 and 20. N. $0^{\circ} 11'$ W., on the N. and S. center line of sec. 17. Descend 55 ft. over NE. slope, through heavy timber and dense undergrowth.
1.60	Dirt road, 10 lks. wide, bears NW., curving to N., and S. 65° E.
11.35	Creek, 2 lks. wide, course N. 35° E.; asc. 75 ft. over SE. slope.
19.60	Same dirt road, bears NE. and SW.
19.71	Point for the center S $\frac{1}{16}$ sec. cor. of sec. 17. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> C S $\frac{1}{16}$ S 17 C 1965 </div> from which A fir, 26 ins. diam., bears N. 46° E., 33 lks. dist., mkd. C S $\frac{1}{16}$ S 17 BT. A fir, 9 ins. diam., bears S. 74° W., $55\frac{1}{2}$ lks. dist., mkd. C S $\frac{1}{16}$ S 17 BT. Ascend 20 ft. over SE. slope.
22.50	Spur, slopes N. 65° E.; desc. 225 ft. over NE. slope, changing to steep N. slope.
30.00	Ravine, drains N. 55° E.; desc. 80 ft. over broken NE. slope.
39.42	Point for the center $\frac{1}{4}$ sec. cor. of sec. 17, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> C $\frac{1}{4}$ S 17 1965 </div> from which

BOOK