Subdivision of Section 17, T. 4 S., R. 7 W.

CHAINS	
	A fir, 28 ins. diam., bears N. 14° E., 85½ lks. dist., mkd. C ¼ S17 BT.
	A fir, 35 ins. diam., bears S. 16° W., 74½ lks. dist., mkd. C ¼ S17 BT.
	Descend 35 ft. over steep NE. slope.
41.00	Top of rock bluff, 60 ft. high, bears NW. and SE.; desc. 175 ft. over bluff and steep NE. slope.
48.00	Low spur, slopes N. 55° E.; desc. 195 ft. over NW. slope, changing to N. slope.
56.30	Bible Creek, 20 lks. wide, course N. 85° W.; asc. 230 ft. over steep S. slope, changing to SW. slope.
61.70	Spur, slopes SW.; desc. 60 ft. along broken W. slope.
65.00	Ravine, drains S. 70° W.; asc. 125 ft. over SW. slope.
73.00	Spur, slopes SW.; desc. 100 ft. over NW. slope.
76.80	Creek, 4 lks. wide, course S. 80° W.; asc. 115 ft. over SW. slope.
79.33	The ¼ sec. cor. of secs. 8 and 17.
	From the ¼ sec. cor. of secs. 16 and 17.
	N. 89° 13' W., on the E. and W. center line of sec. 17.
	Descend 50 ft. over SW. slope, through heavy timber and dense undergrowth.
3.75	Wet ravine, drains S.; asc. 60 ft. over SE. slope.
6.90	Spur, slopes S.; desc. 370 ft. over SW. slope.
20.30	Creek, 1 lk. wide, course S. 10° W.; asc. 15 ft. over SE. slope.
21.00	Top of ascent, slopes S.; desc. 70 ft. over SW. slope.
24.30	Bible Creek, 15 lks. wide, course N. 20° W.; asc. 20 ft. over NE. slope.
32.00	Creek, 2 lks. wide, course N. 50° E.; asc. 240 ft. over steep E. slope, changing to NE. slope.
39.41	The center ¼ sec. cor. of sec. 17.
	Ascend 230 ft. over NE. slope.
57.00	Spur, slopes NW.; desc. 530 ft. over SW. slope.
78.78	The ¼ sec. cor. of secs. 17 and 18.

Remonumentation of a Certain Original Corner Point, T. 4 S., R. 7 W., Willamette Meridian, Oregon

The following field notes describe the remonumentation of a certain original corner point in T. 4 S., R. 7 W., as provided for by the General Special Instructions, Group 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and

96.