



Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains 28.17	Branch, 1 lk. wide, course NW.; asc. 30 ft. over SW. slope.
30.00	Top of ascent, slopes W.; desc. 100 ft. over NW. slope.
34.28	Point for the $\frac{1}{2}$ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mtd.
	
	from which
	A hemlock, 46 ins. diam., bears N. 49° E., 29 lks. dist., mtd. $\frac{1}{4}$ S12 BT.
	A hemlock, 48 ins. diam., bears S. 35° W., 7 lks. dist., mtd. $\frac{1}{4}$ S11 BT.
	Descend 80 ft. over NW. slope.
36.53	Branch, 2 lks. wide, course S. 40° W.; asc. 507 ft. over SE. slope.
51.42	Point for the N 1/16 sec. cor. of secs. 11 and 12. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mtd.
	
	from which
	A fir, 30 ins. diam., bears N. 20° E., 34 lks. dist., mtd. N 1/16 S12 BT.
	A fir, 35 ins. diam., bears S. 45° W., 4 lks. dist., mtd. N 1/16 S11 BT.
	Ascend 4 ft. along E. slope.
52.32	Head of wet ravine, drains SE.; asc. 120 ft. over SE. slope.
56.90	Spur, slopes E.; continue along E. slope.
58.30	Head of ravine, drains SE.; asc. 84 ft. over SE. slope.
60.76	Ridge, bears E. and W., curving to NW.; desc. 34 ft. over NE. slope.
66.10	Head of ravine, drains E.; asc. 45 ft. over SE. slope.
68.56	The cor. of secs. 1, 2, 11, and 12, monumented with the original basalt stone, 36 x 24 x 20 ins., broken and lying on top of ground, with no marks remaining, at record bearing and distance from the original bearing object and bearing tree: A boulder, 8 x 6 x 5 ft., lying on top of the ground, with no marks remaining. A fir snag, 50 ins. diam., bears S. 73 $\frac{1}{2}$ ° W., 115 lks. dist., with no scribe marks visible on badly rotted blaze.